



# RELIABLE EQUIPMENT & SERVICE CO., INC.

REL-4A-2500  
2,500 lbs.

Aluminum Alloy Blocks



REL-3A-1000  
1,000 lbs.

Nylon Fiberglass Di-electric Block



REL-HLB-3  
1,000 lbs.

REL-HLB-3M  
1,000 lbs.  
with optional Meat Hook

## REL-3A-1000

### Lightweight Aluminum Alloy Side Opening Handline Block

The free running 3 inch diameter sheave has a line capacity of 5/8" rope. Features: Sealed roller bearing (upgrade) Swiveling top ring and safety hook. 1,000 lbs. Safe Working Load (SWL) (3-1sf)

IND. EQUIVALENT: 303-B4-PJ

## REL-4A-2500

### Lightweight Aluminum Alloy Side Opening Handline Block

The free running 4 inch diameter sheave has a line capacity of 7/8" rope. Features: Oilite bearing, swiveling top ring and safety hook. 2,500 lbs. Safe Working Load (SWL) (3-1sf)

IND. EQUIVALENT: 404-B2-PJ

## REL-HLB-3 (3M)

### Nylon/Fiberglass Di-Electric HL Block

The free running 3 inch diameter sheave has a line capacity of 5/8" rope. Features: 1/2" dia. axel & swivel bearings Swiveling top ring and safety hook. 1,000 lbs. Safe Working Load (SWL) (3-1sf)

IND. EQUIVALENT: 3550



301 Ivyland Road • Warminster, PA 18974  
Phone: 800-966-3530 • Fax: 215-357-9193

Visit us on the web at [www.Reliable-Equip.com](http://www.Reliable-Equip.com)