



RELIABLE EQUIPMENT & SERVICE CO., INC.



Breather valve allows easy conversion for operation with single acting systems.



Suspension eye allows use for aerial operations



Model	REL-100SDA
Output	100 ton
Weight	95 lbs.
Dimensions	8.25"W x 15"H
Ram Stroke	.98" travel
Oil Capacity	.66 pint



REL-100SDA

100 TON SINGLE/DOUBLE ACTING HYDRAULIC CRIMPING TOOL

The **REL-100SDA** 100 ton press has been designed to compress sleeves and lugs on ACSR and ACAR full tension, transmission and substation connections.

Operable from the **REL-1915** electric/hydraulic pump, **REL-10-I** intensifier, or any 3/4 hp, 10,000 psi hydraulic power source with an adequate reservoir.

Accepts most 100 ton shell type dies currently used with Alcoa, Burndy, and other 100 ton presses. Double acting feature eliminates the possibility of jamming or hanging up.

FEATURES:

- Removable die cap for easy connector positioning.
- 3/8" Screw-type couplers
- Breather valve allows conversion to single acting
- Suspension eye included
- Steel case included
- Long Life Expectancy (tested to 50,000 cycles)



RELIABLE EQUIPMENT & SERVICE CO., INC.

92 Steamwhistle Drive • Ivyland, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193