



# RELIABLE EQUIPMENT & SERVICE CO., INC.

**NEW**  
for 2011



NEW  
"Reliable Grip"  
Handle



Model	REL-1500CH
Capacity:	1,500 lbs.
Travel:	56.5 inches
Hk to Hk	12.4 in. (Min.)
Headroom:	10 inches
Handle:	20.5 inches
Stroke:	33 inches
Weight:	13 lbs.

Manufactured to meet or exceed  
**ASME B30.21.**

**ALSO**  
**REL-2000CH**  
**1 Ton Model**

## REL-1500CH MANUALLY LEVER OPERATED 3/4 TON - LINK CHAIN HOIST

The **NEW REL-1500CH** 3/4 Ton hoist from RELIABLE promises to provide years of dependable service, under the rigorous conditions demanded by the Power Utility & Construction Industries.

The **REL-1500CH** features a field proven ratchet & pawl design for transmission and distribution applications. The high strength ductile aluminum alloy frame and lever assemblies have been constructed and tested to provide smooth and safe operation.

### FEATURES:

The "Reliable Grip" handle provides an added measure of comfort and control during hoist operation.

The Ratchet and Pawl Mechanism provides safe and simple operation in which one pawl is always engaged during lifting and lowering operations.

Chain will not ratchet when lowering if handle is released.

Hoist may be rigged for use in lifting, pulling or binding applications from any position.

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control of the handle.

Standard lift is 5 foot. *Custom lift lengths are available.*



## RELIABLE EQUIPMENT & SERVICE CO., INC.

92 Steamwhistle Drive • Ivyland, PA 18974  
Phone: 800-966-3530 • Fax: 215-357-9193  
Visit us on the web at [www.Reliable-Equip.com](http://www.Reliable-Equip.com)