

RELIABLE EQUIPMENT & SERVICE CO., INC.

NEW



Manufactured to meet or exceed **ASME B30.21.**



REL-1500H REL-3000H

MANUALLY LEVER OPERATED ROLLER CHAIN HOIST

These two **NEW** hoists from RELIABLE promise to provide years of service, under the rigorous conditions demanded by the Power Utility & Construction Industry.

The durable, malleable iron external frame and lever assemblies house internal components constructed and tested to provide smooth and safe operation.

FEATURES:

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

The thumb latch releases chain for fast easy connection to the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control.

The **REL-1500H** has been manufactured to handle a 3/4 ton load with ease.

The **REL-3000H** utilizes a multiple chain configuration to offer a 1-1/2 ton capacity.


The chain lug hook may be detached to provide a longer lift capacity and faster operation in 3/4 ton applications.

Model	REL-1500H	REL-3000H
Capacity:	1,500 lbs.	3,000 lbs.
Travel:	56.5 inches	57 inches
Headroom:	13 inches	15 inches
Handle:	18.75 inches	18.75 inches
Stroke:	27 inches	27 inches
Weight:	18 lbs.	22 lbs.



RELIABLE EQUIPMENT & SERVICE CO., INC.

92 Steamwhistle Drive • Ivyland, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com



RELIABLE EQUIPMENT & SERVICE CO., INC.

NEW
for 2011



Manufactured
to meet or exceed
ASME B30.21.

Model	REL-6000H
Capacity:	6,000 lbs.
Travel:	57 inches
Headroom:	17 1/2 inches
Handle:	27 5/8 inches
Stroke:	42 inches
Weight:	34 lbs.

REL-6000H

MANUALLY LEVER OPERATED 3 TON ROLLER CHAIN HOIST

The **REL-6000H** 3 ton hoist from **RELIABLE** promises to provide years of service, under the rigorous conditions demanded by the Power Utility & Construction Industry.

The durable, malleable iron external frame and lever assemblies house internal components constructed and tested to provide smooth and safe operation.

FEATURES:

The lever action can be reversed simply by releasing the safety pin and rotating handle for inverted applications.

Safety hooks rotate 360° and feature spring latches to simplify a secure connection at the support and the load.

The thumb latch releases chain for fast easy connection to the load.

Slack may be quickly removed by pulling on the free end of the chain.

Redundant safety measures prevent handle rotation or chain release under load if the operator were to lose control.

The **REL-6000H** hoist utilizes a multiple chain configuration to offer a 3 ton capacity.

The chain lug hook may be detached to provide a longer lift capacity and faster operation in 1-1/2 ton applications.



RELIABLE EQUIPMENT & SERVICE CO., INC.

92 Steamwhistle Drive • Ivyland, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193
Visit us on the web at www.Reliable-Equip.com