



# RELIABLE EQUIPMENT & SERVICE CO., INC.

## REL-67BR HYDRAULIC BREAKER



Operate from any  
2,000 PSI Hydraulic  
Power Source

Supplied with  
18 inch whips and  
FF Couplers

Also Available  
REL-45BR  
45 lb. Model

The REL-67BR is a medium-duty T handle hydraulic breaker (70-90 pound class) designed for use in D.O.T and street maintenance, repair of gas & water mains, utility construction, and general contracting applications.

Reliable Equipment has streamlined breaker selection, making your choice simple, while meeting the requirements of your application.

The REL-67BR operates on open-center or closed-center systems and is available with a 1-1/8 or 1-1/4 in. hex chuck.

The feathering feature of the On/Off Valve controls blow speed at Startup making initial tool placement easy.

The diaphragm type accumulator provides consistent, dependable tool operation with system back pressures up to 250 psi (17 bar).

*Steels for breaking, cutting and driving are available from your Reliable representative.*

### SPECIFICATIONS

ITEM	U.S.A.	METRIC
INPUT FLOW RANGE	7 - 9 gpm	26 - 34 lpm
INPUT PRESSURE	1500 - 2000 psi	105 - 140 bar
MAX. BACK PRESSURE	250 psi	17 bar
OPTIMUM FLOW	8 gpm	30 lpm
WEIGHT	67 lbs.	30 kg
LENGTH	27 in.	68 cm
WIDTH (at handles)	16 in.	41 cm

#### STEEL CAPACITY

6 (15.2 cm) x 1-1/8 in. Hex

6 (15.2 cm) x 1-1/4 in. Hex

*Please specify when ordering*

Contact your Reliable representative for a complete listing of steels and accessories.

RELIABLE EQUIPMENT & SERVICE CO., INC.  
301 IVYLAND ROAD • WARMINSTER, PA 18974  
TOLL FREE: 800-966-3530 • FAX: 215-357-9193  
Visit us on the web at [www.Reliable-Equip.com](http://www.Reliable-Equip.com)