



RELIABLE EQUIPMENT & SERVICE CO., INC.

REL-BR-SERIES HYDRAULIC BREAKER



Operate from any
2,000 PSI Hydraulic
Power Source

Supplied with
18 inch whips and
FF Couplers

REL-45BR
45 lb. Model

REL-67BR
67 lb. Model

The REL-BR (45 or 67 lb. Models available) is a medium-duty T handle hydraulic breaker (70-90 pound class) designed for use in D.O.T and street maintenance, repair of gas & water mains, utility construction, and general contracting applications.

Reliable Equipment has streamlined breaker selection, making your choice simple, while meeting the requirements of your application. The REL-BR operates on open- or closed-center systems and is sold standard with a 1-1/8" hex chuck. The 67BR Model is also available with 1-1/4" chuck. The feathering feature of the On/Off Valve controls blow speed at Startup making initial tool placement easy. The diaphragm type accumulator provides consistent, dependable tool operation with system back pressures up to 250 psi (17 bar).

Steels for breaking, cutting and driving are available from your Reliable representative.

SPECIFICATIONS

ITEM	U.S.A.	METRIC
INPUT FLOW RANGE	7 - 9 gpm	26 - 34 lpm
INPUT PRESSURE	1500 - 2000 psi	105 - 140 bar
MAX. BACK PRESSURE	250 psi	17 bar
OPTIMUM FLOW	8 gpm	30 lpm
WEIGHT	45 lb. / 67 lbs.	30 kg
LENGTH	27 in.	68 cm
WIDTH (at handles)	16 in.	41 cm

STEEL CAPACITY

6 (15.2 cm) x 1-1/8 in. Hex

6 (15.2 cm) x 1-1/4 in. Hex

Please specify when ordering

Contact your Reliable representative for a complete listing of steels and accessories.

RELIABLE EQUIPMENT & SERVICE CO., INC.
301 IVYLAND ROAD • WARMINSTER, PA 18974
TOLL FREE: 800-966-3530 • FAX: 215-357-9193
Visit us on the web at www.Reliable-Equip.com