

REL-1915

ELECTRIC HIGH PRESSURE SINGLE/DOUBLE ACTING HYDRAULIC PUMP

The REL-1915 portable Electric High Pressure Hydraulic Power Pump. This intermittent duty two stage pumping system features a high pressure piston style pump, complimented by a low pressure pump for rapid tool advance. The 5/8 HP universal electric motor will operate from any 115V AC power supply.

FEATURES:

- 5/8 HP electric motor
- Two stage pumping system
- 10,000 PSI high pressure pump
- Designed for use with single or double-acting remote tools
- High-pressure relief valve
- Factory filled oil reservoir
- Hand control with 8' cord
- Carrying handle
- Optional carrying case

Electric Motor

5/8 HP, 0.47kw, 3,000 RPM
115V AC 11 Full Load AMPS

Electrical Control

Body mount toggle switch and removable remote hand control with 8 foot twist lock cord.

Oil Delivery Per Minute

160 cubic inches at 100 PSI
30 cubic inches at 10,000 PSI

Oil Reservoir

3 quarts (.75 gallon)



Dimensions


8"W x 8"D x 15"H

Pump Weight W/ Oil

35.72 pounds



Consult your **RELIABLE** representative for more information about our complete line of hydraulic tools.



RELIABLE EQUIPMENT & SERVICE CO., INC.



REL-GB-10 or REL-EP-115 6 HP GASOLINE or 115V ELECTRIC SINGLE & DOUBLE ACTING HYDRAULIC PUMPS

The **REL-GB-10** and **REL-EP-115** single and double acting hydraulic pumps feature manual lever operation, continuous duty performance, and a two stage pumping system, to ensure rapid tool advance.

The manual lever control valve, and factory installed couplers are ready to run your single or double acting crimping, cutting and spearing tools.

RELIABLE EQUIPMENT & SERVICE CO., INC.
92 Steamwhistle Drive • Ivyland, PA 18974
Call: 800-966-3530 • FAX: 215-357-9193
Visit our web sight: www.Reliable-Equip.com

REL-EP-115 - 1 hp electric
115V continuous duty motor.

REL-EP-230 230V model is also available.

REL-GB-10 - 6 HP Briggs/Stratton OHV
4 stroke gasoline engine.

FEATURES:

10,000 PSI high pressure pump.

Fast, two stage pumping system.

Factory filled 2 gallon fluid reservoir
with recessed sight glass.

High-pressure relief valve.

NO CONVERSION NECESSARY

Single/Double selector knob.

Integral manual lever control valve.

Designed for use with high pressure
single & double-acting, hydraulic tools.

REL-GB-10 has a steel support frame.

REL-EP-115 has a balanced carry handle.