



# RELIABLE EQUIPMENT & SERVICE CO., INC.



## SPECIFICATIONS

Pressure	2000 psi Max.
Flow	5-8 gpm (18-30 lpm)
Whip Set	70 inches (178 cm)
Ports	9/16 - 18 SAE O-Ring
Weight	60 lbs. (27.2 kg)
Length	25 1/2 inches (654 mm)

## REL-GRD SERIES “THE DOOGIE DRIVER” GROUND ROD DRIVERS

The REL-GRD **Series** Hydraulic Ground Rod Drivers from **RELIABLE EQUIPMENT** have been designed to drive 1/2 - 5/8, 3/4, or 1 inch galvanized ground rods **FAST**.

Cushioned “Comfort Grip” handles run the length of the tool body providing two handed control while reducing operator fatigue.

The REL-GRD will operate from any Open- or Closed-Center hydraulic system.

70 inch whips with a remote in-line ON/OFF valve provides convenient access to control for accurate drive depth.

The integral lifting eye allows the driver to be lifted and suspended above the rod reducing operator strain.

Flush face quick disconnect couplers are factory installed, so you may use the tool right out of the box.

*Please specify model when ordering.*

REL-GRD-5/8 Drive 1/2”- 5/8” Ground Rod

REL-GRD-3/4 Drive 3/4” Ground Rod

REL-GRD-1 Drive 1” Ground Rod



## RELIABLE EQUIPMENT

CRAFTED WITH PRIDE IN THE U.S.A.  
USED WITH CONFIDENCE AROUND THE WORLD

92 Steamwhistle Drive • Ivyland, PA 18974  
Phone: 800-966-3530 • Fax: 215-357-9193  
Visit us on the web at [www.Reliable-Equip.com](http://www.Reliable-Equip.com)



# RELIABLE EQUIPMENT & SERVICE CO., INC.



70 lbs.  
28.5 in. X 8 in. X 9 in.

## REL-SPD

### HYDRAULIC SIGN POST DRIVER

The **REL-SPD** Sign Post Driver will drive posts of almost any configuration, including "U" channel, round, square, T-post and more.

The **REL-SPD** is fitted to accommodate most common post types, providing greater control throughout the post installation. Reducing operator fatigue due to indirect motion, and limiting damage to the top of the post. A balanced lifting eye, in-line control valve, and dual full length cushion grip handles simplify lifting and operation in raised applications.

Optional post adapters are available to accommodate custom or regional post styles.

The **REL-SPD** meets State Department of Transportation (DOT) requirements for driving breakaway posts and delineators. capable of driving posts to within 4 inches (100 mm) above ground level.

## Capacities

### REL-SPD without accessory adapters

- #2, #3 and #4 lb./ft. "U" Channel Sign Post
- #3 & #4 Strong Back "U" Channel Sign Post
- #1 Delineator Post
- 2-1/2 in. (63.5 mm) Square Post
- 2-5/8 in. (67 mm) Round Post

### REL-SPD with accessory adapters

- 1 3/4" Round (T-Post)
- 1 3/4" Square Post
- 2" Round Pipe
- 2" Square Post
- 2 1/4" Square Post

## RELIABLE EQUIPMENT & SERVICE CO., INC.

92 Steamwhistle Drive Ivyland, PA 18974  
Phone: 800-966-3530 Fax: 215-357-9193  
Visit us on the web at [www.Reliable-Equip.com](http://www.Reliable-Equip.com)

