



RELIABLE EQUIPMENT & SERVICE CO., INC.

SINGLE ACTING HYDRAULIC HOTSTICK EXTENSION

FOR REMOTE HOTSTICK CRIMPING OR CUTTING APPLICATIONS

Optional Easy Lift Handle

MORE CRIMPING AND CUTTING OPTIONS ARE AVAILABLE

REL-510H

HP4707SA

REL-954RC

REL-6TN-RH

REL-10I-SA
S/A INTENSIFIER

**NEW TITANIUM
COMPRESSION HEADS
NOW AVAILABLE!**

REL-HOT-1

Single Acting 10,000 psi Hydraulic Hotstick Extension

This light weight hydraulic extension will accept almost any single acting crimping, cutting, or spearing head for hotstick applications.

A 1-1/4 inch insulated fiberglass pole and an internal non-conductive high-pressure hose assembly allow the operator to work at a safe distance without sacrificing tool control.

Connect the extension to any S/A tool head.

Connect to any high pressure source.

(Gas or electric pump, or intensified tool circuit)

Perform desired task from a safe distance.

Standard length of 6 or 8 foot.

Custom lengths are available.

Consult Reliable for more tool options.

Rubber Gloves, sleeves, and/or protective apparel may be required for optimum operator safety.

Consult the guidelines established by your regulating authority.



RELIABLE EQUIPMENT

USED WITH CONFIDENCE AROUND THE WORLD


92 Steamwhistle Drive • Ivyland, PA 18974

Phone: 800-966-3530 • Fax: 215-357-9193

Visit us on the web at www.Reliable-Equip.com

Tested to meet **O.S.H.A. Reg. #1910.269**





RELIABLE EQUIPMENT & SERVICE CO., INC.

REL-954RC

10,000 PSI HYDRAULIC
CABLE CUTTERS

Lopper Style
Cutting Jaw

Single
Acting



CUT UP TO 954 MCM ACSR



The REL-954RC remote hydraulic cable cutters are ideal for cutting individual conductors or communication cable.

The REL-954RC will cut individual copper to 500 MCM, all-aluminum conductors, and ACSR up to 954 MCM.

Simplicity, speed, and convenience make the REL-954RC cutter the perfect addition to any single-acting tool inventory.

The lopper style blade has been designed to cut the conductor with minimal distortion.

The adjustable jaws will compensate for wear, and to ensure a quality cut with less down time.

When used with the REL-HOT-1 hydraulic extension this tool becomes the perfect tool for Hotstick cutting applications.

MAXIMUM CONDUCTOR CAPACITY

Copper	500 MCM
Aluminum	ALL
ACSR	954 MCM

SPECIFICATIONS

System	SA or DA	
Jaw Opening	1.25 in.	
Force @ 10,000 psi (690 bar)	17,720 lb.	
Return @ 5,000 psi (345 bar)	4,950 lb.	
Max. Operating Pressure	10,000 psi (690 bar)	
Max. Return Pressure	5,000 psi (345 bar)	
Coupler	H/P Screw Type	
Weight: 5.9 lb.	Length: 15 in.	Width: 4 in.

Consult your Reliable representative for additional details.



92 Steamwhistle Drive • Ivyland, PA 18974
Phone: 800-966-3530 • Fax: 215-357-9193

Visit us on the web at www.Reliable-Equip.com