



WC5000H

WC5000H

The WC5000H is the perfect generator to power table saws, small air compressors, saws, and drills. The Honda GX270 will run this generator for over 6.5 hours at full load between refuels. Our Switch-less Full Power™ is standard on this model and allows you to draw the full rated output from a single 120 volt, 240 volt outlet, or a combination of both without switching voltage settings.



WC6000HE

WC6000HE

This 5500 watt continuous, 6000 watt surge generator can start motors up to 3 hp. This allows your crews to operate multiple pieces of equipment and still have enough power to keep the construction site trailer operational. Our Switch-less Full Power™ is standard on this model and allows you to draw the full rated output from a single 120 volt or 240 volt outlet, or a combination of both, without switching voltage settings. This model includes electric start.

MODEL	WC5000H	WC6000H/HE
Maximum Power Rating	5000 Watts	6000 Watts
Continuous Power Rating	4500 Watts	5500 Watts
A.C. Output Voltage	120/240 Volts	120/240 Volts
Continuous Current Rating	37.5/18.8 Amps	45.8/22.9 Amps
Motor Starting Ability (1)	1.5 HP	3 HP
Generator Type (2)	R.F.L.	R.F.B.
ENGINE DATA		
Make/Model	Honda GX270	Honda GX340
Displacement/Type	270 cc/OHV	389 cc/OHV
Conserv-R Automatic Idle Control	Standard	Standard
Low Oil Protection	Standard	Standard
Starting System (3)	Recoil	Recoil or Rec/Elec
Fuel Tank Capacity	7 Gallons	7 Gallons
Running Time - Full Load	10.2 hours	8.1 hours
Hour Meter	Standard	Standard
120 VOLT RECEPTACLES		
Straight Blade (NEMA 5-20R)	4-20 Amp GFCI	4-20 Amp GFCI
Twist Lock (NEMA L5-20R) GFCI Protected	1-20 Amp	1-20 Amp
Straight Blade (NEMA 5-30R)	1-50 Amp	1-50 Amp
120/240 VOLT RECEPTACLES		
Twist-Lock (NEMA L14-30R)	1-30 Amp	1-30 Amp
SIZE & WEIGHT		
Dimensions (LxWxH)	32.7 x 22.9 x 22.1 in.	32.7 x 22.9 x 22.1 in.
Shipping Weight	248 lbs	286 lbs
WARRANTY INFORMATION (4)		
Generator/Engine	2 yrs/3 yrs	2 yrs/3 yrs
CARB Approved	Ye s	Ye s

- Notes:**
- (1) Code G capacitor start motor
 - (2) R.F.B. is a Rotating Field Brush design, R.F.L. is a Rotating Field Brushless design (capacitor excitation) and R.A.B. is a Rotating Armature Brush type generator.
 - (3) Electric start models include battery rack and cables; battery not included.
 - (4) Engine warranty administered by engine manufacturer.

WINCO Inc. continually improves its products and reserves the right to change designs, materials and/or specifications without notice and without incurring any obligations to make such changes or improvements on products previously purchased



TEU1000ID



TEU1000ID – GENERATOR LIGHT

Compact, portable light kit for the **HONDA EU1000I** generator. Lamp folds for compact storage, an Aluminum grid provides lens protection, and teflon separators eliminate heat transmission to handle.



ALL-TERRAIN 2-WHEEL DOLLY KIT

The WINCO 2-wheel dolly kit gives your generator excellent mobility on the ground. The 10" flat free tires get you through mud, snow, sand and soggy lawns. The solid steel axle runs the entire width of the generator providing superior strength. All components are protected from corrosion with our durable baked on powder coat paint system.



16199

ALL-TERRAIN 4-WHEEL DOLLY KIT

The Winco 4-wheel dolly kit gives your generator excellent mobility on the ground without any lifting. The 10" flat free tires get you through mud, snow, sand and soggy lawns. Both solid steel axles run the entire width of the generator providing superior strength. Also features a brake to keep your generator in place. All components are protected from corrosion with our durable baked on powder coat paint system. This dolly kit is available for generators from 6kW-9.5kW.



16199-032

30A TWIST-LOCK PLUG (NEMA L14-30)

The 30 amp twist-lock plug is perfecting for running power into a transfer switch or other distribution box. The cord is sourced locally and specifications should be determined by a competent electrician taking distance, load, and other environmental factors into account.



64492-000

GENERATOR COVER-SMALL

Storage can be hard on your generator. Moisture and dirt can damage the engine and generator windings over time. Often during transport and storage the generator is damaged by scrapes and dents. Winco's heavy tailored canvas cover will protect your generator from these hazards protecting your investment. A built in band keeps the cover in place. This cover is for generators with 2-wheel dolly kits installed.



64444-014

LINE VOLTAGE MONITOR

This compact voltmeter can be plugged in to the 120-volt (NEMA 5-20) receptacle on any WINCO generator to assure you that your generator is functioning properly. Available for most models.



24743-000

BATTERY CHARGER

This battery charger is designed to fully charge a battery and maintain it at proper storage voltage without the damaging effects caused by trickle chargers. Included is a quick connect ring terminal harness for hard to reach areas and alligator clips for an alternate connection.



16287-000

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193

WWW.RELIABLE-EQUIP.COM

