



*Tooling solutions for the power utility industry.*



## 60, 100 & 200 TON COMPRESSION HEADS

### RELIABLE - MODEL EP-60D

The EP-60D double-acting, 60 ton press is designed to compress sleeves and lugs on ACSR and ACAR transmission and distribution cables. Operable from any 10,000 psi pumping source, these tools are made to be portable for easy maneuverability. Accepts any shell type dies currently used with Alcoa or Burndy 60 ton presses. Double acting feature eliminates the possibility of jamming or connector hang up.

**EP-60DT (Titanium) 40% lighter than model above.**



### RELIABLE - EP-100WB & EP-200WA

The EP-100WB and EP-200WA are 100 and 200 ton compression heads for full tension, transmission and substation connections.

The **EP-100WB** will accept shell type dies currently used with Alcoa 100 ton compression heads. 200 ton dies are considered special application and must be engineered to the connector manufacturer's specifications. Consult factory for these dies.

These compression heads are double-acting, and designed to operate from the REL 554, PPE 1020, REL-10-I or any 3/4 hp, high-pressure, double-acting pump with the proper oil capacity.

### FEATURES:

- ✓ **Lightweight**
- ✓ **Removable die cap for easy connector positioning.**
- ✓ **Tool stand included (EP-60D)**
- ✓ **3/8" Screw-type couplers**
- ✓ **Carrying case included (EP-60D)**



| MODEL        | EP-60D      | EP-100WB       | EP-200WA     |
|--------------|-------------|----------------|--------------|
| Output       | 60 ton      | 100 ton        | 200 ton      |
| Weight       | 47 lbs.     | 96 lbs.        | 190 lbs.     |
| (Titanium)   | 34 lbs.     | N/A            | N/A          |
| Size         | 5"W x 17"H  | 7-1/2"W x 14"H | 14"W x 17"H  |
| Ram Stroke   | 1.5" travel | .98" travel    | 1.57" travel |
| Oil Capacity | 303 cc      | 314 cc         | 1134 cc      |

**TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193**