



Tooling solutions for the power utility industry.

4244 - Voltage Detector



4315 Shotgun Adapter



4315 Storage Case



AUDIO/VISUAL VOLTAGE DETECTOR

For overhead A.C. voltages from 240V to 500kV
Verify Live or De-energized Conductors.
 Each tester comes complete with batteries and a splined universal end fitting.

It is recommended that the tester be moved progressively closer to conductor or apparatus until warning of voltage is indicated or until it touches the conductor or apparatus.

Part	Dimensions	Settings
4244	11" x 3.5"	Off/240V/4.2kV/15kV 25kV/35kV/69kV/230kV
4344	11" x 3.5"	Off/240V/4.2kV/35kV/69kV 115kV/230kV/345kV/500kV
4356	Complete kit - 4244 unit, case and adaptor	
4367	Complete kit - 4344 unit, case and adaptor	

TIF-8800



UL Classified
MSHA
Approved

TIF-300hv



UL Classified
MSHA
Approved

TIF - 8800 - LEAK DETECTORS

The TIF8800 series are general purpose combustible gas detectors which may be used where a combustible gas, vapor, or residue needs to be found.

Features:

- Unique flexible 15" stainless probe**
- Automatic warm-up**
- Rechargeable Ni-Cad batteries**
- Low battery indicator**
- Sensitivity Adjust control**
- Audible "Geiger counter" signal**
- Broad band detection**
- Recharger and ABS**
- Carry case included**

REL-TIF 300HV TIC TRACER™ AC VOLTAGE DETECTORS

Tic Tracers detect the electrostatic field generated around an AC conductor. This permits safe, non-contact voltage detection.

The REL-TIF 300hv is the deluxe version of the Tic Tracer line. This instrument allows for high voltage testing and adds a visual indicator. Adaptable to TIF's Hot Sticks. Perfect for load-break connectors and checking transmission lines. Low range 30 to 1,500VAC, High range for 1,500 to 122,000VAC!

OPTIONAL

- | | |
|-------------|-----------------|
| REL-TIF 303 | - CARRY CASE |
| REL-TIF 310 | - 36" HOT STICK |
| REL-TIF 410 | - 48" HOT STICK |

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193