



Tooling solutions for the power utility industry.

HAND LINE BLOCKS

Blocks and sheave constructed of rugged nylon fiberglass reinforced high di-electric material.

Reinforced 1/2" diamter axle and swivel bearings.

3" sheaves - block can accommodate rope thru 5/8" dia.

Provided with either side opening or closed block.

Blocks are rated with 3-1 safety factor.*

Part	Weight	Description
3550	1-3/4 lbs.	Side Opening Block w/ Swivel Hook and Safety Snap
3551	1-3/4 lbs.	Closed Block w/ Swivel Hook and Safety Snap
3553	1-1/4 lbs.	Side Opening Block w/ Swivel Eye Only
3554	1-1/4 lbs.	Closed Block w/ Swivel Eye Only
3550-1	1-3/4 lbs.	Side Opening Block w/ Swivel Meat Hook
3551-1	1-3/4 lbs.	Closed Block w/ Swivel Meat Hook
10-147	1 lb.	Meat Hook only for blocks

*Recommended safe working load 1,000 lbs.



Hand Line Hook

P-10060 - HAND LINE HOOK

Constructed from manganese bronze alloy.

Use with up to 1/2" rope.

Rated at 600 lbs. working load.

P-30142 - HAND LINE SNAP

Constructed of drop forged alloy steel.

5,000 lb. proof load.

5/8" snap opening. (1" dia. hole)



Hand Line Snap



**IF YOU DON'T SEE WHAT YOU NEED
CONTACT RELIABLE EQUIPMENT
800-966-3530**

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193