

*Tooling solutions for the power utility industry.***IRWIN POLE BITS - TAPER SQUARE SHANK W/ ADAPTER SECTION**

- Single twist type with single spur, cutter and side lip, and a Medium-fast screw pitch.
- Hollow center twist design for fast, continuous flow of chips
- Designed to bore through creosoted poles without clogging, binding or stopping to clear chips. Equally efficient for boring large timbers used in heavy construction.
- Heat-treated full length for extra strength.

IRWIN POLE BIT		8" TWIST				12" OVERALL LENGTH				
SIZE	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/16"
Part	-	46509	-	46511	-	46513	-	-	-	-
		12" TWIST				18" OVERALL LENGTH -				
SIZE	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/16"
Part	46608	46609	46610	46611	46612	46613	46614	46615	46616	16617
		18" TWIST				24" OVERALL LENGTH				
SIZE	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/16"
Part	-	-	-	46711	-	46713	-	-	46716	-

Sizes 11/16" through 1-1/16" have 5/16" hex shanks.

**THE FIREBALL - Carbide-Tipped Pole Bits**

The double-spur, carbide-tipped, hex-shanked bit has been tested and refined over many years of in-the-field use. THE FIREBALL is specified by many major public utility companies for drilling CCA and creosoted power poles.

THE FIREBALL will outlast and outperform wood boring bits that are not carbide-tipped by a wide margin. The FIREBALL utilizes an especially designed tip configuration that results in faster drilling, and can be resharpened or completely replaced. The hardened lead screw is also replaceable allowing these bits to be completely rebuilt if necessary.

With the 7/16" hex-drive shank these bits can be used in either electric, air, or hydraulic driven impact wrenches. A 1/2" capacity drill motor can also be used. A 1/2" drive impact socket shank is available on request. **Also available in 5/8" Hex.**

FIREBALL		7/16" HEX			8" TWIST		12" OVERALL LENGTH			
SIZE	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/16"
Part	-	H70809	-	H70811	-	H70813	-	H70815	-	H70817
		7/16" HEX 12" TWIST			16" OVERALL LENGTH					
SIZE	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/16"
Part	-	H71209	-	H71211	-	H71213	-	H71215	-	H71217
		7/16" HEX 18" TWIST			22" OVERALL LENGTH					
SIZE	1/2"	9/16"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/16"
Part	-	H71809	-	H71811	-	H71813	-	H71815	-	H71817

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193

*Tooling solutions for the power utility industry.***GREENLEE NAIL EATER II IMPACT BITS**

- Quickly bore through creosoted and salt treated utility poles.
- Patented new design for improved cutting and cleaner holes.
- Self-feeding screw point draws bit through wood.
- Unique patented design cutting angle - smoother starts, reduced cutting loads.
- Made of super tough heat treated steel; cuts through nails and provides longer life.

Electric drill required: 61 PTS- 5/8" through 61 PTS- 1", min. 3/8" drill; All Big Shank, 1/2" drill.

NAIL EATER II		7/16" HEX *			15" TWIST			18" OVERALL LENGTH		
SIZE	*1/2"	5/8"	11/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/8"	1-1/4"
PART	30915	30919	30921	30923	30925	30927	30929	30931	30935	30937

**IRWIN POWER POLE AUGER BITS**

- Single twist type with single spur, cutter, and side lip.
- Hollow center twist design for fast, continuous flow of chips. Medium-fast screw pitch.
- For boring creosoted poles and construction timbers and multiple timber applications.
- Heat-treated full length. Guaranteed consistent Rockwell hardness.
- Bores smooth clean holes for installing bolts and pins.
- 7/16" Hex shank fits all adjustable 1/2", 3-jaw chucks and No. 43907 bit extension.
- 5" shank has 1-3/4" of 1/2" round and 1-3/4" of 7/16" hex.
- Cut off hex section and use 1/2" round shank if job requires.

IRWIN POWER POLE AUGER BITS					12" TWIST			17" OVERALL LENGTH		
Size	9/16"	5/8"	1-1/16"	3/4"	13/16"					
Part	46809	46810	46811	46812	46813					
IRWIN POWER POLE AUGER BITS					18" TWIST			23" OVERALL LENGTH		
Size	9/16"	5/8"	1-1/16"	3/4"	13/16"	7/8"	15/16"			
Part	46909	46910	46911	46912	46913	46914	46915			
IRWIN POWER POLE AUGER BITS					24" TWIST			29" OVERALL LENGTH		
Size	9/16"	5/8"	1-1/16"	3/4"	13/16"	7/8"	15/16"	1"	1-1/16"	
Part	47009	47010	47011	47012	47013	47014	47015	47016	47017	



**IF YOU DONT SEE WHAT YOU NEED
CONTACT RELIABLE EQUIPMENT
800-966-3530**



TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193





Tooling solutions for the power utility industry.

RELIABLE EQUIPMENT - POLE BITS

Hollow center twist design, single spur cutter and side lip for fast continuous flow of chips.

			
IMPACT 18" OVERALL LENGTH 12" TWIST - 7/16" HEX		IMPACT 18" OVERALL LENGTH 12" TWIST - 5/8" HEX	
47909	9/16"	48109	9/16"
47911	11/16"	48111	11/16"
47913	13/16"	48113	13/16"
47915	15/16"	48117	1-1/16"

			
GAS DRILL 17" OVERALL LENGTH 12" TWIST		BIT BRACE 18" OVERALL LENGTH 12" TWIST	
47309	9/16"	47109	9/16"
47311	11/16"	47111	11/16"
47313	13/16"	47113	13/16"
47315	15/16"	47115	15/16"
47317	1-1/16"	47117	1-1/16"



POLE STEP DRIVER

PSD-2-7/16", OR PSD-2-5/8"

Heavy-duty construction permits faster driving and extraction of pole steps. Heat-treated, high tensile steel, for use in impact wrench.



POLE STEP DRIVER

"J" HOOK PULLER

BJH-1-7/16", OR BJH-1-5/8"

For easy installation and removal of "J" Hooks. Made of heat-treated, high tensile steel, for use in impact wrench.

We maintain complete inventories to assure you prompt delivery. For further information on these and other products, please contact our sales department.



"J" HOOK PULLER



Tooling solutions for the power utility industry.

HAND LINE BLOCKS

Blocks and sheave constructed of rugged nylon fiberglass reinforced high di-electric material.

Reinforced 1/2" diameter axle and swivel bearings.

3" sheaves - block can accommodate rope thru 5/8" dia.

Provided with either side opening or closed block.

Blocks are rated with 3-1 safety factor.*

Part	Weight	Description
3550	1-3/4 lbs.	Side Opening Block w/ Swivel Hook and Safety Snap
3551	1-3/4 lbs.	Closed Block w/ Swivel Hook and Safety Snap
3553	1-1/4 lbs.	Side Opening Block w/ Swivel Eye Only
3554	1-1/4 lbs.	Closed Block w/ Swivel Eye Only
3550-1	1-3/4 lbs.	Side Opening Block w/ Swivel Meat Hook
3551-1	1-3/4 lbs.	Closed Block w/ Swivel Meat Hook
10-147	1 lb.	Meat Hook only for blocks

*Recommended safe working load 1,000 lbs.



Hand Line Hook

P-10060 - HAND LINE HOOK

Constructed from manganese bronze alloy.

Use with up to 1/2" rope.

Rated at 600 lbs. working load.

P-30142 - HAND LINE SNAP

Constructed of drop forged alloy steel.

5,000 lb. proof load.

5/8" snap opening. (1" dia. hole)



Hand Line Snap



**IF YOU DON'T SEE WHAT YOU NEED
CONTACT RELIABLE EQUIPMENT
800-966-3530**

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193