



Tooling solutions for the power utility industry.



CUMALONGS

The exclusive wedge-grip action provides a positive, tight grip on the conductor for non-kinking, in-line pull. Kearney Cumalongs are easily installed and removed with a tie stick. When the tie stick is removed from the ring, the safety latch drops over the conductor slot to keep the Cumalong on the conductor.

For faster, easier operation, right and left hand styles enable the lineman to always have the conductor slot facing him. All models except 16847 Series include hardened steel rollers for easier opening and positive holding. Wedges are bronze, except 1833-14 (Steel) and 130429 (Aluminum).

Bodies are Aluminum, except 1833-2 and -3 (Bronze).


16847



1833-3



130428-1



Part No.		Conductor Range		Max. Working Load	Repl. Wedge
Left	Right	Max.	Min.		
16847	16847-1	2-7 str.-.292"	8 sol.-.128"	2,000	16960
1833	1833-1	4/0 ACSR-.563"	8 sol.-.128"	4,000	1833-14
1833-2	1833-3	4/0 ACSR-.563"	8 sol.-.128"	6,000	1833-14
1833-4	1833-5	*795 ACSR-1.050"	2 sol.-.258"	5,500	1833-44
1833-22	1833-21	954 Str.-1.126"	4/0 ACSR-.563"	5,500	1833-24
—	130428	1590 ACSR-1.545"	266.8 str-.586"	15,000	135105-1
—	130428-1	1590 ACSR-1.545"	266.8 str-.586"	4,000	130429

NOT FOR USE WITH GUY WIRE

*795 ACSR when diameter of specific stranding does not exceed 1.050"



**IF YOU DON'T SEE WHAT YOU NEED
CONTACT RELIABLE EQUIPMENT
800-966-3530**

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193