



Tooling solutions for the power utility industry.

43180 - OVERHEAD CIRCULAR SAW

Use for high production utility line clearing and general municipal applications*.

Super Spool™ selector control for Open- and Closed-Center systems.

Safety features include: hand stop safety collar, trigger guard, two-step safety trigger, and branch stop.

Rugged gear motor.

Angular head design makes flush cuts easier and directs chips away from the operator.

9" diameter blade standard.



SPECIFICATIONS:

Cutting Capacity: 3.5 in.

Blade Diameter: 9 in.

Extension Type: Fiberglass

Weight: 9 lbs.

Overall Length: 82 in.

Flow Range: 4-6 gpm

Operating Pressure: 1,000-2,000 psi

Pressure Port Thread: 3/8" NPTF

Return Port Thread: 3/8" NPTF

RPM: 5,250 rpm @ 6 gpm

*** CAUTION** Not to be used for ground level operation.

SAW ACCESSORIES

PART	DESCRIPTION	USE WITH TOOL					
		38568	43177	43178	43178	H6200B	43180
F022545K	Bar					x	
48683	11" Bar	x	x	x	x		
170074	13" Bar	x	x	x	x		
48265	16" Bar	x	x	x	x		
F022544	Chain					x	
48682	11" Chain	x	x	x	x		
F030030	13" Chain	x	x	x	x		
48266	16" Chain	x	x	x	x		
107941	Sheath - 15"					x	
107940	Sheath - 12"	x	x	x	x		
L088009	9" Blade						x
F0173461	Spanner Wrench					x	
107387	Fiberglass Scabbard For Use on Bucket Trucks					x	
48337	Bar Tip Guard	x	x	x	x	x	

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193