



*Tooling solutions for the power utility industry.*



## H6245 - CUT-OFF SAW - OPEN-CENTER

Easily cuts concrete, stone, or steel when equipped with the appropriate blade (blade not included).

Comes complete with a water hose port.

24 in. whip hoses.

Auxiliary handle.

Rugged gear motor.

Adjustable debris guard.

Optional three wheel cart available.

**Weight:** 21 lbs.

**Length:** 26.5 in.

**Width:** 5.5 in.

### Specifications:

**Cutting Capacity:** 5.25 in. with 14 in. blade

**Blade Diameter:** 14 in. max.

**Arbor Shaft Diameter:** 1 in.

**Flow Range:** 5 - 8 gpm

**Operating Pressure:** 1,000 - 2,000 psi

**Blade Speed:** 4,100 rpm at 8 gpm

**Pressure and Return Port Thread:**

3/8 NPTF (Tool), 1/2 NPTF (Hose End)

## CUT-OFF SAW ACCESSORIES

**F019329** 14 in. Metal Blade

**F019330** 14 in. Concrete Blade



## 137125 - CUT-OFF SAW CART

Optional three-wheel cart for use with H6245.  
(Saw not included with cart)

For precision depth control and straight line cutting from a standing position.

Single clamp mounting feature for quick mounting or removal of the saw from the cart.

Removable handle - allows cuts to be made within 3 in. of an obstruction.

### Specifications:

**Length:** 27-1/2 in.

**Width Across Handle:** 19-1/2 in.

**Width Across Wheels:** 14-1/2 in.

**Height:** 36-3/4 in.

**Weight:** 59 lb.

**Wheel Diameter:** 6 in.

**TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193**