



Tooling solutions for the power utility industry.



REL-SAC - VALVE CONVERTER

Converts the PVA-1122 valve from a double acting to a single acting valve for use with all existing single acting tools supplied with a 3/8" female type coupler.

Adapter simply screws into place re-directing pressure to single line output.



RELIABLE - 3VE3 & 3VE4

HIGH PRESSURE HYDRAULIC HOSE

10,000 psi (40,000 psi min. burst) high pressure hydraulic hose designed and tested to meet the electrical conductivity requirements established in the utility market. The 3VE3 series is a 3/16" I.D. hose, standard in most double acting applications, and the 3VE4 series, which is 1/4" I.D., is more common in single acting applications.

FEATURES: H/D thermoplastic construction, certified non-conductive, assemblies available in any length, Lightweight, wear resistant, and excellent weatherability. Temperature range from -40°F to +150°F, H/D hose guard provides greater hand and body protection. Safety orange jacket for greater operator awareness. Hoses are tested at 75kV/ft assuring that the hose has a leakage factor of less than 50 microamperes.

PART	DESCRIPTION	PART	DESCRIPTION
*3VE3-72	3/16" x 6' H.P. HOSE	**3VE4-120	1/4" x 10' H.P. HOSE
*3VE3-96	3/16" x 8' H.P. HOSE	**3VE4-300	1/4" x 25' H.P. HOSE
*3VE3-120	3/16" x 10' H.P. HOSE	**3VE4-600	1/4" x 50' H.P. HOSE
*3VE3-300	3/16" x 25' H.P. HOSE	Consult your Reliable Rep. for add'l, options.	

* Each hose above includes hose guards and 1/4" MPT ends. 8.1 lbs. Wt. / 100 ft.

** Each hose above includes hose guards and 3/8" MPT ends. 10.6 lbs. Wt. / 100 ft.

HIGH PRESSURE COUPLINGS

COUPLERS			DIMENSIONS			
PART	BODY	THREAD	Overall	Hex	Dia.	
3050-2	1/4"	1/4-18	2.38"	1.06"	1.13"	
3050-3	3/8"	3/8-18	2.88"	1.06"	1.20"	
NIPPLES			Overall	Exposed	Hex	Dia.
3010-2	1/4"	1/4-18	1.29"	0.48"	0.75"	1.13"
3010-3	3/8"	3/8-18	1.58"	0.50"	0.94"	1.25"



TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193