RELIABLE EQUIPMENT

Tooling solutions for the power utility industry.

SIGN POST DRIVER

One person operation.

Drives a variety of post sizes and configurations.

Dual carrying handles.

Lifting eye.

Reversible on/off valve for Open- and Closed-Center Systems.

H4825C 3.8 in. diameter post capacity

H4825C1 2.5 x 4 in. rectangular post capacity

Specifications:

Valve Location: Hose End Mounted

Flow Range: 5 - 7 gpm

Operating Pressure: 1,000 - 2,000 psi On/Off Valve Pressure Port Thread:

9/16 - 18 SAE O-Ring

On/Off Valve Return Port Thread:

3/4 - 16 SAE O-Ring

Blows Per Minute: 1,800 @ 6 gpm

Weight 59 lbs. Length 30"

Width 9"

H4876A - HEAVY DUTY SIGN POST DRIVER

Open- or Closed-Center System

Heavy duty - Ideal for DOT and street departments.

Designed to be boom mounted.

With interchangeable adapter can be used as a driver or a concrete breaker.

3/4 in. diameter lifting eye.

12 in. whip hoses included.



Post Capacity: 2.75 in. diameter

Valve Location: Remote Flow Range: 7 - 9 gpm

Operating Pressure: 1,000 - 2,000 psi


Pressure Port Thread: 9/16 - 18 SAE O-Ring (Tool),

1/2 NPTF (Hose End)

Return Port Thread: 3/4 - 16 SAE O-Ring (Tool),

1/2 NPTF (Hose End)

Blows Per Minute: 1,200 @ 8 gpm



Weight 83 lbs.
Length 31"
Width 7.5"

TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193