



Tooling solutions for the power utility industry.

PPE-1020 - ELECTRIC / HYDRAULIC PUMP

Operate both single- and double-acting tools from this 1/2 hp, 6.5 amp @ 120 VAC pump unit provides up to 10,000 psi hydraulic power for high-pressure cutting and crimping tools.

This compact unit allows use of double-acting cutting and crimping tools in construction situations where hydraulic systems may not be available. Features a built-in relief valve and high-pressure couplers.

SPECIFICATIONS: System: Open-Center, Reservoir Capacity: 0.5 gal., Relief Valve Setting 10,000 psi, Output Flow @ 10,000 psi is 18.8 in. 3/min., Fast Advance Flow 0.7 gpm, Weight: 28 lb., 9.5" O.A.L., Width: 7.5", Height: 15.5", H/P Port 1/4-18 NPSM



GASOLINE POWERED / HYDRAULIC PUMPS

10-GM

4 hp four-cycle gasoline engine

Three-stage pump for rapid (2) ram advance

3-way valve for single acting operation

10,000 psi high-pressure pump

Selector for single or double acting mode (4-way option)

High-pressure safety relief valve

Carrying handle

Factory filled oil reservoir

Pressure matched quick-coupler(s) supplied

Optional: Operating pressures, 4-way manual valve for double acting operation, and carrying case.



30-GS-4

7 hp four-cycle gasoline engine

Two-stage pump for rapid ram advance

10,000 psi high-pressure pump

4-way Solenoid valve with remote hand control with 8 foot cord

Selector Valve for single or double acting modes

High-pressure safety relief valve

Protective carrying frame

Factory filled oil reservoir

Pressure matched quick-couplers supplied

Optional: Operating pressures, 4-way manual valve for double acting operation, and remote foot control.



TO ORDER CALL: 800-966-3530 OR FAX: 215-357-9193