



CHANCE EPOXIGLAS^R TELESCOPING DISCONNECT TOOLS

The telescoping tube design uses heavy duty spring-loaded plastic buttons to keep the extended sections securely locked in position. As each section is extended and twisted slightly, the buttons pop into place, allowing work to be done with complete control and confidence.

The tip section of the heavy duty unit is slightly larger in diameter (1-1/4" ver. 1-1/16") so that each telescoping tube is slightly larger, resulting in a more rigid tool when extended.

The universal end fitting on the insulated top section accepts a variety of attachments, so that the lineman can disconnect switches, replace cutout tubes, and reclose, remove pole covers, prune trees, replace bulbs, and complete many other overhead tasks . . . all with one tool.

STANDARD DUTY (1-1/16" DIA. TIP)

Part	Ext. Length (locks at ea. length)	Retracted Length	Base Dia.	No. of Sections	Wt.
C403-1023	8'	56"	1-1/4"	2	2 lb.
C403-1017	8', 12'	57"	1-1/2"	3	2.75 lb.
C403-1018	12', 16'	59"	1-11/16"	4	4 lb.
C403-1019	12'6", 16'6", 20'	61"	1-7/8"	5	5.25 lb.
C403-1020	16'6", 20'6", 25'	63"	2-1/16"	6	7 lb.
C403-1021	17'6", 21'6", 25'6", 30'	65"	2-1/4"	7	8.75 lb.
C403-1022	22', 26', 30'6", 35'	67"	2-1/2"	8	11 lb.

COMPACT STANDARD DUTY (1-1/16" DIA. TIP)

Part	Ext. Length (locks at ea. length)	Retracted Length	Base Dia.	No. of Sections	Wt.
T403-2205	5', 6'6", 8'	29-1/2"	1-7/8"	5	2.75 lb.
C403-1739	14', 17', 20', 23'	48"	2-1/2"	8	9 lb.

HEAVY DUTY (1-1/4" DIA. TIP)

Part	Ext. Length (locks at ea. length)	Retracted Length	Base Dia.	No. of Sections	Wt.
C403-1597	8'	56"	1-1/2"	2	3 lb.
C403-1598	8'-12'	57"	1-11/16"	3	3.75 lb.
C403-1599	12'-16'	59"	1-7/8"	4	5 lb.
C403-1600	12'6"-16'6"-20'	61"	2-1/16"	5	6.5 lb.
C403-1601	16'6"-20'6"-25'	63"	2-1/4"	6	8.5 lb.
C403-1602	17'6", 21'6", 25'6", 30'	65"	2-1/2"	7	10.25 lb.

*To include tool bag, add suffix "A" to part number.

NOTE: Individual replacement parts as well as complete repair kits are available to extend the life of your valuable Telescoping Disconnect Tools. Consult your Reliable Equipment representative for further information.