



*Tooling solutions for the power utility industry.*

## HASTINGS - TEL-O-POLE<sup>®</sup>

Teloscopic hot stick for long reach, speed, convenience, and safety.

100% tested per OSHA and ASTM F-711.

All new safety Corona discharge head.

For opening and closing disconnect switches.

Replacing fuse in porcelain type cut-outs.

Pruning tree limbs.

All sections are of reinforced high density electrical grade fiberglass laminate with unusual color stability, greater strength and high dielectric properties.

Tubular sections are engineered to allow for air circulation - condensate and moisture is not trapped when stick is retracted.

Universal head is adaptable to standard fit on accessories.

Disconnect hook is standard equipment.

Tip section is triply reinforced to eliminate breakage.

All parts are standardized for easy field repairs.

Stick can be disassembled for cleaning.

### PATENTED INTERLOCK FEATURE

Stick may be locked in lengths listed by means of one pin locking two or more sections. To engage locking pin, extend section to its limit and turn for hole alignment.

### STANDARD TEL-O-POLE HOT STICK

Model	Extended	Retracted	Base Dia.	Tip Dia.	Weight
S-208	8 Ft.	25"	1-7/8"	7/8"	2.75 lbs.
S-212	12 Ft.	44"	1-5/8"	7/8"	3.75 lbs.
S-216	12' 4", 16'	56"	1-5/8"	7/8"	4.5 lbs.
S-220	17', 20'	58"	1-7/8"	7/8"	5.5 lbs.
S-225	17', 21', 25'6"	60"	2-3/16"	7/8"	7 lbs.
S-230	17', 21'6", 26', 30'	61-5/8"	2-3/8"	7/8"	8.75 lbs.
S-235	17', 21'6", 26', 30', 35'	63-3/8"	2-11/16"	7/8"	11 lbs.

Stick can be locked at each length listed. (Tip section will not interlock.)

THE HOT STICK YOU  
CAN PUSH, PULL AND TWIST  
SURE-LOCK JOINTS  
CAN'T SLIP OR COLLAPSE!



Unicellular foam filled tip sections



Corona Free Discharge Heads





**IF YOU DON'T SEE WHAT YOU NEED  
CONTACT RELIABLE EQUIPMENT  
800-966-3530**