



*Tooling solutions for the power utility industry.*



**CHANCE - GRIP-ALL CLAMPSTICKS - Single-Piece Style**

The Grip-All stick puts an easy-to-control “finger” on an insulated pole. Although primarily designed for installing hot-line and grounding clamps, it serves both overhead and underground circuits with various end fittings. Commonly called a “shotgun,” the operating mechanism incorporates a sliding hand grip that opens the hook to grasp a clamp eyescrew and retract it into the tool head. A safety thumb latch then must be depressed to release the locked hand grip so it can open the hook. While the tool head is of Lexan<sup>®</sup> for close-quarter operations, the worker must maintain recommended working distance solely on the Epoxiglas<sup>®</sup> pole section of the handle as the hook and its actuator are metal parts.

Easy to care for, Grip-All sticks do not require field stripping to clean. All insulated parts including the operating rod are outside the main pole, readily accessible to wipe dry.

**CAUTION:** Do not clean the plastic head with solvent.

Part	Description	Wt.	Part	Description	Wt.
C403-0291	1-1/4" x 4' 5"	5.75	C403-0294	1-1/4" x 10' 5-1/2"	8.00
C403-0292	1-1/4" x 6' 5-1/2"	6.50	C403-0295	1-1/4" x 12' 5-1/2"	8.75
C403-0293	1-1/4" x 8' 5-1/2"	7.25	-	-	-

**CHANCE - GRIP-ALL CLAMPSTICKS - Telescoping Style**

This Telescoping Grip-All Stick may replace several conventional clampsticks. It permits linemen to serve their many safe-working distances and positioning needs while conserving valuable storage space.

Engineered interface between sections ensures that tool retracts with full control. Close fit also helps keep out dirt and moisture. Top section is of foam-center Epoxiglas<sup>®</sup> insulated pole.

Basic clampstick functions of this telescoping style are identical to the fixed-length style. All controls can be manipulated while wearing gloves. Easy to disassemble, the Telescoping Grip-All Stick must be kept clean and dry inside and out for maximum personnel protection.

Part	Extended Tool will lock at each length	Retracted	Weight
C403-1035	5' 6-3/4", 6' 9-1/2", 8'	5' 2-3/4"	6 lb.
C403-1036	8' 6-3/4", 10' 4-1/2", 12' 2-1/4", 14'	8' 2-3/4"	8 lb.

**Telescoping Style with Universal Fitting on Handle**

Part	Extended Tool will lock at each length	Retracted	Weight
C403-3060	5' 6-3/4", 6' 9-1/2", 8'	5' 2-3/4"	6 lb.
C403-3061	8' 6-3/4", 10' 4-1/2", 12' 2-1/4", 14'	8' 2-3/4"	8 lb.

\* For information on additional clampstick options and storage bags consult your Reliable Equipment representative.